
HOTSOAK 62




HOTSOAK SERIES MODEL # AI3AIR7236HS

















SPECIFICATIONS:

GENERAL SPECIFICATIONS:

Tub Size

71 1/4" x 36" x 23 1/4"

181 cm x 91 cm x 59 cm

Bathing Well 48 1/2" long

24" wide

21 3/4" interior depth

Shipping Weight
Tub Weight Filled
Tub Only Weight
Tub Only Weight
Gallons to Overflow
Tub Only Weight
Tub Only

ELECTRICAL SPECIFICATIONS:

Pump 1/15 HP; 1.3 AMP; 110V
Heater 1.5 kW; 12.5 AMP; 110V
Requirements 20 AMP; 110V, separate circuit required protected w/ Class A GFCI

This unit is not recommended for shower installations.

STANDARD EQUIPMENT:

Aquatic Quality Features:

- 1.5 kW Inline Maintenance Heater
- Run-Dry Pump with 20-Minute Timer
- 2 Circulation Portal Covers
- Bath-Side On/Off Electronic Button
- "Quiet Pad" Anti-Vibration Pump Mount for Quiet Operation
- Raised Seat
- Slip Resistant Floor
- 2 Arm Rests
- Extra Deep and Long Bathing WellPre-leveled ABS Support Base
- Pre-leveled ABS Support Base
- $\hbox{-} \mbox{ Heat-bent Rigid PVC Piping for Optimum Sanitary Conditions} \\$
- Durable, Easy to Clean, Lucite $^{\footnotesize @}$ Cast Acrylic Surface
- Available in 8 Standard No-Charge Colors

UL & IAPMO Listed, Factory Tested Limited Lifetime Warranty

OPTIONAL EQUIPMENT:

- Chromatherapy LED Lighting*
- Comfort Pillow Oval or Rectangle
- Bolt-On Grab Bar
 - White, Biscuit, Chrome, Polished Brass, Gold,
 Polished Nickel, Satin Nickel or Oil Rubbed Bronze
- Lift & Turn Waste and Overflow
 - Chrome, Polished Brass, Gold, Polished Nickel, Satin Nickel or Oil Rubbed Bronze
- Cable Drive Waste and Overflow
 - Chrome, Polished Brass, Gold, Polished Nickel, Satin Nickel, Oil Rubbed Bronze or Color Matched (Bone, White and Biscuit Only)
- Factory Installed Rigid ABS Tile Flange
- Color Matched Acrylic Skirt
- · Premium Colors

All acrylic colors featured by Aquatic match the industry's leading fixture manufacturers.

*This whirlpool will need to be hard wired to the breaker box. Three outlets will be supplied on the whirlpool.

Fax-On-Demand Document # 1237



The manufacturer accepts a 1/4" variance. There are variations on each tub and specifications are subject to change as we improve upon our product as required. The dimensions needed for site preparation and structure building should be measured from the tub; Aquatic Industries, Inc. assumes no responsibility for preparatory work.

www.aquaticwhirlpools.com 800.555.5324